









MILK™ Series

Food Grade
PVC Liquid Suction Hose

MILK-LT™ Series

Low Temperature Food Grade PVC Liquid Suction Hose

General Applications:

- Food grade liquids such as milk, beer, wine and juice
- Ice transfer
- Milk and dairy product transfer
- Water suction standard duty

Construction: PVC tube with rigid PVC helix.

Service Temperature Range (MILK):

-4°F (-20°C) to +150°F (+65°C)*

Service Temperature Range (MILK-LT):

-40°F (-40°C) to +150°F (+65°C)*

Features and Advantages:

- Precision Controlled ID and OD Dimensions Facilitates insertion of sanitary fittings.
- Food Grade Materials Hose complies with applicable FDA⁽⁰³⁾ and 3-A⁽⁰¹⁾ requirements. Hose complies with applicable USDA⁽¹²⁾ requirements.



- "Cold-Flex" Materials (MILK-LT only) Hose remains flexible in severe sub-zero temperatures.
- Transparent Construction "See-the-flow."
 Allows for visual confirmation of material flow.
- Smooth Outer Cover Provides increased pressure rating and smooth surface for banding.
- Phthalate Free

Nominal Specifications											
Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius	Standard	Woight
	(in)	(mm)	(in)	(mm)	68°F	104°F	68°F	104°F	at 68°F (in)	Length (ft)	Weight (lbs/ft)
MILK150	1-1/2	38.1	1.79	45.5	75	50	Full	26	4	100	0.45
MILK200	2	50.8	2.33	59.2	75	50	28	25	6	100	0.63
MILK250	2-1/2	63.5	2.87	73.0	55	40	28	24	10	100	0.81
MILK300	3	76.2	3.42	86.9	55	40	28	24	11	100	1.18
MILK-LT150	1-1/2	38.1	1.79	45.5	75	50	Full	26	4	100	0.45
MILK-LT200	2	50.8	2.33	59.2	75	50	28	25	5	100	0.65
MILK-LT250	2-1/2	63.5	2.87	73.0	55	40	28	24	8	100	0.84
MILK-LT300	3	76.2	3.42	86.9	55	40	28	24	11	100	1.20

NOTE: Service life may vary depending on operating conditions and type of material being conveyed.

NOTE: For details of the following compliances, refer to footnotes listed on page 63.

*Actual service temperature range is application dependent.